

# XT-D 300

WASTE OIL HEATER

**LANAIR**  
WASTE OIL-FIRED  
HEATERS & BOILERS



Heats up to  
**10,000** sq. ft.



Up to  
**300,000** BTU



Now burns  
**100% synthetic oil**  
along with other used fluids (see back)

**Factor in unstable fuel prices and escalating disposal costs and you'll see why purchasing a Lanair XT-D Series Heater is indeed "The Right Choice at the Right Time!"**

The XT-D 300 Waste Oil Heater now burns 100% used synthetic oil and comes standard with an easy access hinged chamber door for easy clean out. It also features a large clean-out side-access panel to the collector box. Some of the new improvements made to the XT-D models are: easy to remove burner, a noncontinuous spark transformer, an hour meter, and a prime switch. All of these features make it easy for those who compare...buy Lanair!

# XT-D 300

## WASTE OIL HEATER



### HOW MUCH IS YOUR USED OIL WORTH?

Use our savings calculator on [lanair.com](http://lanair.com) to find out how much green you will save while protecting the environment.

SELECT YOUR CURRENT HEATING SOURCE.

NATURAL GAS

ELECTRIC

PROPANE

#2 FUEL OIL

Facility produces  gallons of waste oil each year:

---

By the end of your first year you could save:

**\$5,105**

Cost per gallon to dispose of waste oil \$

Amount you can put back in your pocket

**\$1,250**

Number of years you would like to see savings for:

---

Over the course of  Years you could save:

**\$63,550**

## PRODUCT SPECIFICATIONS

Heat Range (BTUH)*	Up to 300,000
Fuel Input (GPH)	2.1
Fuel Type†	Used crankcase oil up to 50 wt (conventional or synthetic), used automatic transmission fluid, #1 and #2 fuel oil (diesel)
Heating Area (sq. ft.)**	Up to 10,000
Power Supply (AC)***	(2)-120 V-60Hz 2 Legs
Cabinet Dimensions (L x W x H)	47" x 46" x 36"
Hanging Weight (lbs.)	696
Chimney Pipe****	8" Class A
Compressed Air*****	2 CFM – 15-18 PSI
Combustion Chamber	10 Gauge CRS
Ductable Option	Yes
Chimney Location	Top and left side

\* BTUH value varies with fuel type.

\*\* The suggested heating area is based on building with minimal heat loss due to open door, construction, materials, windows, insulation, etc.

\*\*\* With optional compressor 30 amp breaker with 10 gauge wire is required.

\*\*\*\* Chimney package sold separately.

\*\*\*\*\* Customer supplied. Air source must be capable of producing 2.0 CFM @ 30 PSI to secondary air filter regulator.

† Stay away from gear lubes. They do not burn and will cause additional maintenance for your waste oil heater.

Hazardous waste is illegal to burn in a waste oil heater.

The EPA of the USA does not allow the burning of brake fluid, and it is illegal to burn in a waste oil heater.

There is no UL safety standard for the burning of used cooking oil (vegetable oil) at this time. It should not be burned.

Note: International customers should check their local regulations, as "what you can legally burn" may change.

Lifetime Tech Support (via phone)

Lanair App

1-Year/10-Year Limited Warranty (parts/chamber)

UL and ULC Listed



4109 Capital Circle Dr.  
Janesville, WI 53546

email: [sales@lanair.com](mailto:sales@lanair.com)

(800) 562-5504  
Fax: (608) 757-7878

[lanair.com](http://lanair.com)

PN 81010653